



H.264 Network Camera

Model No.: Tayama-320C

Features:

- No IP address needed when used in LAN.
- No Public IP address needed when used on Internet.
- Integrate both Network camera and DVR / NVR functions.
- NVR function can support 100+ channels of Intranet and Internet IP cameras.
- The NVR system manages and records both Intranet and Internet IP cameras.
- View real-time and playback video on both Intranet and Internet.
- Display up to 128 channels of video images.
- Streaming multi-channel videos.



Specifications:

Model	Tayama-320C	
OS	Embedded Linux	
Encoder	H.264 Base Line	
Sensor	SONY 1/3" CCD	
Process	Interlaced	
Resolution	D1, CIF, QCIF	
Max FPS	D1 @ 25/30 FPS	
Bit Rate	16K-4Mb, Adjustable	
V. Stream	8 video streams	
Lens	f=4-9 mm	
Min Lux	0.5/ 0.01 Lux	
IR Allowed	no	
AWB	Auto	
Gain	Auto	
Backlight	Auto	
Standard	PAL or NTSC	
Audio	Encoder	GSM
	Bit rate	13K bps
	Connector	n/a
Network	RJ-45	10/100 Base-T
	Wireless	(Optional)
	Protocol	TCP/IP, UDP, HTTP, RTP, RTCP, RTSP, DHCP, PPPOE
Storage	SD slot	Micro SD up to 32GB
Power	Voltage	DC 12V
	POE	(Optional)
	Watt	< 5W
Temp	-10°C ~ 60°C	
Dimension (Φ x H)	Φ 5.9" x 5.2" (Φ 150 x 132 mm)	
Weight	2.6 lb (1200g)	

Design and specifications are subject to change without prior notice.